


HAIR VAC SILO

HAIR CLIPPER VACUUM



HAIR CLIPPER VACUUM SERIES

Hair Vac Silo Standard Specifications

Vacuum Producer - Three Phase / Continuous Duty 24/7 Operation

- Multi-stage centrifugal turbine produces more suction using less horsepower than any other in its class
- TEFC motor is maintenance free and rated for continuous duty
- Inclusive sound suppression (silencers) lower dB below 85 dB

Durable Housing:

- Compression cast composite housing will not dent, break or rust and there is no need for painting
- Carbon impregnated housing is chemically neutral and static dissipating (<10 Ohms to eliminate static discharge)
- Housing is modular to accommodate filter upgrades and is backed by our lifetime warranty

Superior MicroClean Filtration:

- Ruwac's industry-leading MicroClean filtration is 99.99% efficient at 0.5 microns
- Ensures that hair waste will not clog the filter system
- Depending on motor size, filter sizes range from 13 sq. ft. to 48 sq. ft.

Low Maintenance:

- 30 gallon, powder coated drum is easily removable for quick dumping
- Plastic bag liners provide hygienic clean-ups.



Product	# of Chairs	Volts	CFM	Hp	Dimensions
NS150	3 - 4	208, 230 / 460V	150 CFM	3 Hp	85.62"x23"
NS180	5 - 6	208, 230 / 460V	180 CFM	3 Hp	85.62"x23"
NS300	8 - 10	208, 230 / 460V	300 CFM	5 Hp	85.62"x23"
NS380	10 - 12	208, 230 / 460V	380 CFM	7 Hp	N/A
NS500	12 - 14	208, 230 / 460V	500 CFM	10 Hp	N/A

ADDER	DESCRIPTION
Barber Chair System	Includes 2" Tubing, Elbows, Inlets and Clipper w/ Vacuum Hose and Inlet Adapter
Remote Starter	Remote Starter Control Panel w/ 24 V fused relay. NEMA 4 Enclosure.
Single Phase Adder	Single Phase Adder for 2 HP and 3 HP, 208, 230 V Single Phase
CY90132104R	Vacuum Clipper with Shroud
CY9013201	Vacuum Clipper Hose w/ Connection to Inlet Valve
CY90132104	Vacuum Clipper w/ Shroud and Hose
CY901325P	Shroud for Wahl Clipper, Plastic
CY901326P	Shroud for Oster Clipper, Plastic
CY701210	Chrome Steel Inlet Valve