

REDLINE PRO XLT

SEPARATE + EXTRA CAPACITY
CYCLONE + SURFACE PREPARATION SERIES

STANDARD SPECIFICATIONS: HEC-XLT PRO

- Powerful 240 Volt, Single Phase, 4 motor - 453 CFM, 60 Hz and 97" H2O
- 28 ft² MicroClean Primary Filter - 99% Efficient @ 0.5 Microns
- Mechanical Filter Cleaning Mechanism for Dustless Cleaning
- HEPA 2.0 Secondary Filter - 99.97% Efficient @ 0.3 Microns
- 2 3/4" Inlet Connection with Aluminum Cast Deflector
- 9 Gallon, Foot Lever Actuated Dustpan for Dustless Emptying
- 6" Heavy Duty Casters
- Compression Cast **"BULLETPROOF"** Composite Modular Housing
- Advanced "Rapid Cool" Heat Displacement

HEC-XLT PRO



PRE-SEPARATOR

www.ruwac.com
RUWAC USA

THE FINE DUST EXPERTS

Contact us today for pricing and availability

413-532-4030

OSHA COMPLIANCE TABLE:

- Up to (2) 7" handgrinders
- Up to (2) 7" tuck pointers
- Up to (2) 7" handheld crack chasers
- 10" shotblasters
- 13" scarifiers
- Up to 32" walk-behind floor grinders
- Joint cleanout saws
- Up to (2) 8" handheld power saws for fiber board
- Dowel drilling rigs